

TENT TUNNELS 3.00 M

ARCH: built in one single piece of **ø 40 x 1.5 mm sendzimir Z275 galvanized tube**, calendered in three points to create the "tent" shape. The load-bearing capacity is guaranteed in the case of snow and resistance in the event of wind.

CONNECTION LINES: there are three connection lines made of **ø 30 x 1.2 mm sendzimir Z275 galvanized tube**. One is positioned near the ridge, while the other two are just below the sloping roof curves. In order to allow the correct locking of the arches, without any drilling, the tubes are fixed with special joints called "springs" and "pens".

CROSS BRACING: made of **ø 30 x 1.2 mm sendzimir Z275 galvanized tube**, they are very important elements for the stability of any structure. They are always placed in an oblique position at the four corners, between the first and the second arch.

SHEETING HEADS: the standard version includes a wide door measuring 1.10 m x 2.00 m in height made of tube **ø 30 x 1.2 mm sendzimir Z275 galvanized tube**

The polyethylene sheet is used for the covering.

ROOF: This structure is normally covered with a simple transparent polyethylene sheet that has exceptional transparency, an excellent thermal effect and high mechanical characteristics.

The sheet can be fixed directly to the supporting structure, using simple clips, in **DACROMET** galvanized steel or through the use of a safe combination of aluminium profiles and PVC raceways.

LOMBARDA SERRE S.r.l.

Via Prà delle Vigne, 191 - 21030 GRANTOLA (VA) – ITALY

Tel. (+39) 0332.57.65.56 – Fax (+39) 0332.57.67.70

Varese Companies Register N° 374656 – Tax Code / VAT No. 03727770129

e-mail: info@lombardaserre.it – website: www.lombardaserre.it

LATERAL OPENINGS: Just roll the sheet up to the desired height to obtain effective ventilation of the side walls of the tunnel. It is the most widely used solution for greenhouses and is certainly the simplest and most economical.

Edging with a height of 50 cm is also provided, made up of a choice of fibreglass or alveolar polycarbonate, which prevents air infiltrations near the base of the cultivations. It also acts as a containment system of the internal soil of the tunnel. Special iron hooks and specific green polyethylene rope complete the application.

